

V-Bank Glide/Pack®



Advantages

- V-bank design reduces filter velocity and filter pressure drop by up to 60%, saving energy
- Increases life of filters up to four times

Typical applications: Single-stage V-bank filter housing for commercial, industrial, manufacturing or medical facilities.

Construction: 16-gauge galvanized steel with pre-drilled standing flanges, dual access doors, UV-resistant door knobs, door and filter sealing gasketing.

Filters: Any 2" deep filter.

Performance: Less than 1/2 of 1% leakage guaranteed. Rated airflow 500 fpm, may be operated to 625 fpm. Standard model operational to ± 6.0" w.g.

Additional data: Sizes available from 4 filters high to 6 filters wide. Housing is weatherproof for outside installation without modification. Includes pneumatic fitting for static pressure gauge.

See Product Sheet 2421 for more details.

Dimensions and Airflow Capacity (cfm)

Number of Filters Wide	Height (inches)	1/2 Filter Wide	1 Filter Wide	1-1/2 Filters Wide	2 Filters Wide	2-1/2 Filters Wide	3 Filters Wide	3-1/2 Filters Wide	4 Filters Wide	4-1/2 Filters Wide	5 Filters Wide	5-1/2 Filters Wide	6 Filters Wide	Housing Depth (inches)	
1/2	15.25	-	2,000	-	4,000	-	6,000	-	8,000	-	10,000	-	12,000	28.00	
1	27.25	2,000	4,000	6,000	8,000	10,000	12,000	14,000	16,000	18,000	20,000	22,000	24,000		
1-1/2	39.50	-	6,000	-	12,000	-	18,000	-	24,000	-	30,000	-	36,000		
2	51.50	4,000	8,000	12,000	16,000	20,000	24,000	28,000	32,000	36,000	40,000	44,000	48,000		
2-1/2	63.75	-	10,000	-	20,000	-	30,000	-	40,000	-	50,000	-	60,000		
3	75.75	6,000	12,000	18,000	24,000	30,000	36,000	42,000	48,000	54,000	60,000	66,000	72,000		
3-1/2	88.00	-	14,000	-	28,000	-	42,000	-	54,000	-	70,000	-	84,000		
4	100.00	8,000	16,000	24,000	32,000	40,000	48,000	56,000	60,000	72,000	80,000	88,000	96,000		
Width (inches)		12	24	36	48	60	72	84	96	108	120	132	144		

As part of our program for continuous improvement, Camfil Farr reserves the right to change specifications without notice.