

Housings (ASHRAE)

3P Glide/Pack®



Advantages

- Less than 1/2 of 1% leakage guaranteed
- Housing efficiency equal to the applied filtration efficiency

Typical applications: Two-stage filter housing for commercial, industrial, manufacturing or medical facilities.

Construction: 16-gauge galvanized steel with pre-drilled standing flanges, dual access doors, UV-resistant door knobs, door and filter sealing gasketing and a pneumatic tap for installation of static pressure gauge.

Filters: Any 2" deep prefilter with any 4", 6", or 12" final filter, or multi-pocket filter as the second stage.

Performance: Rated airflow 500 fpm, may be operated to 625 fpm. Standard model operational to ± 6.0" w.g.

Additional data: Sizes available from 4 filters high to 6 filters wide. Housing is weatherproof for outside installation without modification. Available with insulation, primed for painting, or in stainless steel construction. Consult factory.

See Product Sheet 2401 for more details.

Dimensions and Airflow Capacity (cfm)

Number of Filters High	Height (inches)	1/2 Filter Wide	1 Filter Wide	1-1/2 Filters Wide	2 Filters Wide	2-1/2 Filters Wide	3 Filters Wide	3-1/2 Filters Wide	4 Filters Wide	4-1/2 Filters Wide	5 Filters Wide	5-1/2 Filters Wide	6 Filters Wide	Housing Depth (inches)	
1/2	15.25		1000		2000		3000		4000		5000		6000	21.00	
1	27.25	1000	2000	3000	4000	5000	6000	7000	8000	9000	10000	11000	12000		
1-1/2	39.50		3000		6000		9000		12000		15000		18000		
2	51.50	2000	4000	6000	8000	10000	12000	14000	16000	18000	20000	22000	24000		
2-1/2	63.75		5000		10000		15000		20000		25000		30000		
3	75.75		6000	9000	12000	15000	18000	21000	24000	27000	30000	33000	36000		
3-1/2	88.00		7000		14000		21000		28000		35000		42000		
4	100.00		8000	12000	16000	20000	24000	28000	32000	36000	40000	44000	48000		
Width (inches)		12	24	36	48	60	72	84	96	108	120	132	144		

As part of our program for continuous improvement, Camfil Farr reserves the right to change specifications without notice.