

Type 8 Built-up Bank Filter Holding Frame



Advantages

- Universal filter acceptance, any filter from 1" deep to 36" deep with the application of specific fasteners
- May be assembled into banks up to six frames high by any number wide
- Leak free system integrity, ensuring that all of the air moving through the system will be treated by the filter
- Multiple stages of filters can be installed on each frame

Typical applications: Built-up bank frames for installation in HVAC applications in commercial, industrial, manufacturing and medical facilities.

Construction: 16-gauge galvanized steel frame with gasketed filter seal flange, multiple lances for application of various fasteners to accommodate any 1" deep filter and up to 36" deep of multiple filter stages. Pre-drilled holes for bank assembly, marked top for ease of installation.

Filters: 1" MERV 6 to 12" deep MERV 15 filters. May also be used with adsorbent panels or modules.

Additional data: Available in stainless steel, consult factory.

See Product Sheet 2301 for more details.

| Model Number | Actual Depth (inches) | Actual Height (inches) | Actual Width (inches) | Weight (lbs.) |
|---------------------------------------|-----------------------|------------------------|-----------------------|---------------|
| For Built-up Bank Applications | | | | |
| 079473-004 | 2.69 | 24 | 12 | 4.3 |
| 079473-006 | | 20 | 16 | 4.4 |
| 079473-005 | | 25 | 16 | 5.0 |
| 079473-002 | | 20 | 20 | 4.9 |
| 079473-003 | | 25 | 20 | 5.5 |
| 079473-007 | | 24 | 20 | 5.4 |
| 079473-001 | | 24 | 24 | 6.0 |

As part of our program for continuous improvement, Camfil Farr reserves the right to change specifications without notice.